



MAIN FEATURES

P/N	XPTN-9000-85-1GH4GP-VX
Fixed port	1*2.5G Base-X, 4*10/100/1000 Base-T
Management	Yes
PoE Support	Yes
Input Voltage	DC12-58V(Non-PoE), DC48~58V(PoE)
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Thermal methods	Fanless design, natural cooling
MTBF	100,000 hours
Authentication	CCC/CE/FCC/RoHS

SPECIFICATION

Provider Mode Ports

Fixed port	1*2.5G Base-X, 4*10/100/1000 Base-T
Management Port	Support console
Power interface	Phoenix terminal, redundant dual power supply
LED Indicators	PWR, Link/ACT LED

Cable Type & Transmission Distance

Twisted-pair	0-100m (CAT5e,CAT6)
Monomode optical fiber	20/40/60/80/100 Km
Multimode (optical) fiber	550 m

Network Topology

Ring topology	Support
Star topology	Support
Bus topology	Support
Tree Topology	Support
Hybrid topology	Support

Electrical Specifications

Input voltage	DC12-58V(Non-PoE), DC48~58V(PoE)
Total Power consumption	<10W(Non-PoE), <130W(PoE)

PoE Support

PoE port	1-4
PoE Protocol	802.3af, 802.3at
Pin Assignment	1,2,3,6
PoE Management	Support

Layer 2 Switching

Switching capacity	36G
--------------------	-----

Packet forwarding rate	26.78 Mpps
MAC address table	16K
VLAN	Support 4K
Buffer	12M
Forwarding delay	<10 μs
MDX/MIDX	Support
Flow control	Support
Jumbo Frame	Support 10 Kbytes
Spanning Tree	Support STP/RSTP/MSTP
Ring Protocol	Support ERPS
Link Aggregation	Support 12 group
Multicast	Support IGMP Snooping
Port Mirroring	Support
Storm Control	Support
Interface Counters	Support
QINQ	Support
WatchDog	-
802.1X	Support
MAC Authentication	Support
Port Isolation	Support
Rmon	Support
NTP client	-
DHCP CLIENT	Support
DHCP snooping	Support
PING/TRACEROUT	Support
Dying gasp	Support
DDM	Support
Port Isolation	Support
Convergence	
ACL	Support ACL 500; Support IP standard ACL; Support MAC expand ACL; Support IP expand ACL
QoS	Support QoS re-marking, priority mapping; Support SP, WRR queue scheduling; Support egress rate-limited, egress rate-limit; Support Policy- Based QoS
Management	
CLI	Support
Console	Support
Telnet	Support
WEB management	Support
Management IP	Support IPV4/IPV6
SNMP	Support SNMPv1/v2c/v3
User Management	Support
System Log	Support
Configuration File Download/Upload	Support
Upgrade Firmware	Support

Environment	
Operating temperature	-40°C ~ +75°C The device is tested for 8 hours at temperatures in 85°C
Storage temperature	-40°C ~ +85°C
Relative humidity	5% ~ 95% non-condensing
Thermal methods	Fanless design, natural cooling
MTBF	100,000 hours
Mechanical Dimensions	
Product size	65*104*143 mm
Installation Method	DIN-rail
Weight	0.85 Kg
EMC & Ingress Protection	
IP Level	IP50
Surge protection of Power	IEC 61000-4-5 Level X (10KV/10KV) (8/20 μs)
Surge protection of Ethernet port	IEC 61000-4-5 Level X (6KV/4KV) (10/700 μs)
RS	IEC 61000-4-3 Level 3 (10V/m)
EFI	IEC 61000-4-4 Level 3 (1V/2V)
CS	IEC 61000-4-6 Level 3 (10V/m)
PFMF	IEC 61000-4-8 Level 4 (30A/m)
DIP	IEC 61000-4-11 Level 3 (10V)
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Free fall	0.5m
Authentication	
Authentication	CCC/CE/FCC/RoHS
Accessories	
Accessories	Device, Terminals, Specification, Certificate; Adapter (Optional)

SIZE AND APPEARANCE

