



MAIN FEATURES

P/N	XPTN-9000-63-1FX1TX-SC-mini
Fixed port	1*100 Base-FX, 1*10/100 Base-TX
Management	No
PoE Support	No
Input Voltage	DC12-58V
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Thermal methods	Fanless, natural cooling
MTBF	100,000 hours
Certificates	CCC/CE/FCC/RoHS

SPECIFICATION

Provider Mode Ports

Business interface (Fixed port)	1*100 Base-FX, 1*10/100 Base-TX
Management Port	None
Power interface	Phoenix terminal, dual power supply
LED Indicators	P1/P2, OPT

Cable type & Transmission distance

Twisted-pair	0-100m (CAT5e, CAT6)
Monomode optical fiber	40KM
Multimode optical fiber	550m

DIP Switch

1 LFP	LFP/ Remote PD Reset
2 LGY	LEGACY (Standard & Non-standard PoE)
3 VLAN	Port Isolation
4 BSR	Storm Control Configuration

Network Topology

Ring topology	Unsupported
Star topology	Support
Bus topology	Support
Tree Topology	Support
Hybrid topology	-

Electrical Specifications

Input voltage	DC12-58V
Total Power consumption	<5W

PoE Support	
PoE port	None
PoE Protocol	None
Pin Assignment	None
PoE Management	-
Layer 2 Switching	
Switching capacity	1G
Packet forwarding rate	0.744 Mpps
MAC address table	2K
Buffer	768K
Forwarding delay	<5 μ s
MDX/MIDX	Support
Flow control	Support
Jumbo frame	2K bytes
Storm Control	Support
Port-Isolation	Support
Remote PD Reset	Support
Environment	
Operating temperature	-30°C~+75°C
Storage temperature	-30°C~+75°C
Relative humidity	10%~90% (non-condensing)
Thermal methods	Fanless, natural cooling
MTBF	100,000 hours
Mechanical Dimensions	
Product size	91*118*31mm (W×H×D)
Installation Method	DIN-rail
Weight	0.36 Kg
EMC & Ingress Protection	
IP Level	IP40
Surge protection of Power	IEC 61000-4-5 Level 3 (4KV/2KV) (8/20 μ s)
Surge protection of Ethernet port	IEC 61000-4-5 Level 3 (4KV/2KV) (10/700 μ s)
RS	IEC 61000-4-3 Level 3 (10V/m)
EFI	IEC 61000-4-4 Level 3 (1V/2V)
CS	IEC 61000-4-6 Level 3 (10V/m)
PFMF	IEC 61000-4-8 Level 4 (30A/m)
DIP	IEC 61000-4-11 Level 3 (10V)
EMI	CLASS A
ESD	IEC 61000-4-2 Level 4 (8K/15K)
Free fall	0.5m
Authentication	

SIZE AND APPEARANCE

